

DATA SHEET

TESIRAFORTE® X 400

MEETING ROOM DSP



TesiraFORTE® X 400 is a meeting room DSP featuring multiple network and analog audio connection points, with 4 channels of Acoustic Echo Cancellation (AEC) assignable across any digital or analog input. Five 1 Gigabit Ethernet ports are provided, four of which are PoE+ powered, and all of which support media and control traffic of various types including AVB, Dante™, and VoIP.

A USB port also supports 1x1 mono or 2x2 stereo USB audio along with HID synchronization allowing the device to act as a conferencing audio peripheral to systems such as Biamp's Modena™ family or Unified Communications platforms.

Biamp Launch™ technology provides the capability for device discovery and tuning to be undertaken without the need for custom programming, and additionally provides the user with a full performance report of the space upon completion.

TesiraFORTE X 400 provides extensive audio processing, including but not limited to: AEC technology, signal routing and mixing, equalization, filtering, dynamics, and delay, as well as control, monitoring, and diagnostic tools. TesiraFORTE X 400 is auto-configurable using Biamp Launch but also allows users the option to manually override and completely customize its programming using Tesira software.

FEATURES

- Supports simultaneous operation of AVB, Dante, and AES67 digital audio networking protocols
- 2 mic/line level inputs, 2 mic/line level outputs
- Five 1 Gigabit Ethernet ports
- Four ports support PoE+ power (IEEE 802.3.at Class 4, 30W)
- Up to 2x2 channels of configurable USB audio
- 4 AEC channels assignable to any input
- 4-pin GPIO
- Surface mountable with included bracket
- Supports port authentication via IEEE 802.1X
- SIP VoIP interface via Gigabit Ethernet connection
- CE marked, UL listed, and RoHS compliant
- Covered by Biamp Systems' 5-year warranty

Biamp, Tesira, Modena, and TesiraFORTE are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Audinate and Dante are either trademarks or registered trademarks of Audinate Pty Ltd in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.

ARCHITECTS & ENGINEERS SPECIFICATION

The Conference Room DSP shall support Ethernet connection for programming and control on a RJ-45 connector. The Conference Room DSP shall have internal DSP processing. The Conference Room DSP shall include 4 channels of General Purpose Input and Output connection (GPIO) for sending or receiving logic signals. The programming of the GPIO ports shall be software configurable. The Conference Room DSP shall include a Universal Serial Bus (USB) connection on a standard USB-B type connector. The Conference Room DSP shall be software configurable to stream up to 2 channels of digital USB Class 1 Audio transmission either into or out of the Conference Room DSP or simultaneous input and output. The Conference Room DSP shall support port authentication via IEEE 802.1X. The Conference Room DSP shall provide 2 balanced input connections for receiving of microphone or line level analog audio signals on screw-down, removable connectors. Any network audio or analog audio connection may be assigned one of four channels of Acoustic Echo Cancellation (AEC). Acoustic Echo Cancellation (AEC) hardware and firmware, the parameters, routing and operation of which shall be software programmable. The Conference Room DSP shall provide 2 balanced output channels for the transmission of microphone or line level analog audio signals on screw-down, removable connectors. Each individual channel shall have its own dedicated connection. The Conference Room DSP shall integrate to Voice Over Internet Protocol (VoIP) systems on a RJ-45 connector and shall support Session Initiation Protocol (SIP) v2.0 or later. The Conference Room DSP shall be capable of being deployed with zero programming or manual tuning and shall provide a post-commissioning status report via the use of Biamp Launch technology. The Conference Room DSP shall feature software-configurable signal processing, including but not limited to: signal routing and mixing, equalization, filtering, dynamics, and delay, as well as control, monitoring, and diagnostic tools. The Conference Room DSP shall provide front panel LED identification of device power, status, alarm, and activity as well as system-wide alarm. The Conference Room DSP shall be surface mountable using the included mounting hardware. The Conference Room DSP shall be CE marked, UL listed, and shall be compliant with the RoHS directive. Warranty shall be five years. The Conference Room DSP shall be TesiraFORTÉ® X 400.

TESIRAFORTÉ X 400 SPECIFICATIONS

Frequency Response: 20Hz to 20kHz, +4dBu output: +0.25 dB/-0.5 dB		Crosstalk, channel to channel, 1 kHz: 0dB gain, +4dBu input: < -85dB 54dB gain, -50dBu input: < -75dB	
THD+N (22Hz to 22kHz): 0dB gain, +4dBu input: < 0.006% 54dB gain, -50dBu input: < 0.040%		Sampling Rate: 48kHz	
EIN (no weighting, 22Hz to 22kHz): < -125dBu		A/D - D/A Converters: 24-bit	
Dynamic Range (in presence of signal) 22Hz to 22kHz, 0dB gain: > 108dB		Power Consumption: 100-240VAC 50/60Hz: < 150W	
Input Impedance (balanced): 8kΩ		USB: Bit Depth: 16-bit / 24-bit Number of Channels: up to 2x2 Sample Rate: 48kHz	
Output Impedance (balanced): 207Ω		Environment: Ambient Operating Temperature Range: 32-104° F (0-40° C) Humidity: 0-98%, non-condensing Altitude: 0-6,600 feet (0-2000 Meters) MSL	
Maximum Input: +24dBu		Compliance: FCC Part 15B (USA) Canada ICES-003 (A) / NMB-003 (A) CE marked (Europe) UL und C-UL listed (USA and Canada) RCM (Australia) RoHS Directive (Europe)	
Maximum Output (selectable): +24dBu, +18dBu, +12dBu, +6dBu, 0dBu, -31dBu			
Maximum Number of AVB Channels: 128x128			
Maximum Number of AVB Streams: 64x64			
Maximum AVB Stream Passthrough: 150			
Maximum Number of Dante Channels: 32x32			
Maximum Number of Dante Flows: 32x32			
Input Gain Range (6dB steps): 0-66dB			
Overall Dimensions: Height: 1.47 inches (37.3 mm) Width: 8.11 inches (206 mm) Depth: 8.11 inches (206 mm) Weight: 1.9 lbs (0.86kg)			
Phantom Power: +48VDC (7mA/input)			

TESIRAFORTÉ X 400 BACK PANEL



OPTIONAL ACCESSORIES

C5E-10-P, C5E-25-P – 10ft and 25ft pre-terminated plenum rated Cat 5e cables

RMX 100 – Universal Rack Shelf

Plenum Box 12x12 – Chicago compliant plenum box

PEX – 50 ft (15m) power extension cable



A: 9300 S.W. Gemini Drive Beaverton, OR 97008 USA

T:

W:

TESDS-396-2104-EN-R2